

VW3620 CPU Module

VW-CPU

The VW-CPU can be installed in the ATEN VW3620 36 x 20 Modular 4K Video Wall Processor, which features two CPU board slots. The upper slot is running as the primary by default. Each VW-CPU is equipped with an individual 10/100/1000Base-T LAN port and controller card which enables efficient transmission and management of data. VW-CPU comes hot-standby that standby CPU will automatically backup and switch as primary to resume the logic workings and IO control from the previous stopped when the primary CPU shuts down. It can take over the primary system operation immediately to guarantee easy maintenance of interface need constant uptime. These highlights have made the VW754 ideal for mission-critical scenarios that involve via Web GUI without shutting down the current display on the video wall. Consequently, VW-CPU supports redundancy to ensure uninterrupted operation for any mission-critical video wall applications.



Specifications

	VW-CPU
Control	
Ethernet	1 x RJ-45 Female, 10/100/1000Base-T
Power Consumption	9.95W:47BTU
	<p>Note:</p> <ul style="list-style-type: none">• The measurement in Watts indicates the typical power consumption of the device with no external loading.• The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Operating Temperature	0 – 40 °C
Physical Properties	
Housing	Metal
Dimensions (L x W x H)	19.30 x 27.10 x 2.74 cm
Weight	0.78 kg
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

