

4-Port True 4K HDMI Splitter

VS4814

Brilliant True 4K, Effortlessly Multiplied
across Four Streams



The VS4814 distributes a single HDMI source to four displays simultaneously, delivering stunning True 4K visuals. It features EDID Sync™ for flawless audiovisual synchronization and HDCP 2.2 compliance to guarantee reliable visual performance. Supporting HDR10+, 3D formats, and Deep Color, it offers richer contrast and a wider color spectrum for truly immersive viewing. Its sleek, compact, and user-friendly design makes it ideal for modern digital signage, commercial display applications, and home entertainment setups.




HDMI
HIGH-DEFINITION MULTIMEDIA INTERFACE



Accent Light



Compact
Design



18Gbps Max.
Bandwidth

Features

EDID Sync™ Smart Display Optimization

Automatically optimizes resolutions and prevents display issues for flawless display presentation

True 4K Dual-Display Sharing

Shares one HDMI source across two True 4K displays for double the visual impact with uncompromised quality

HDMI 3D/Deep Color, HDR10+, HDCP 2.2 Compatible

Guarantees stable performance, broad compatibility, and superior image quality


Master-Class Audio Immersion

Full support for LPCM 7.1, Dolby® & DTS-HD Master Audio™ delivers theatrical-quality surround sound

Aesthetic Compact Form

Slim profile and stylish accent lighting allow integration into any space, perfectly complementing your setting


Installation



Specifications

Video Input	
Interfaces	1 x HDMI Type-A Female (Black)
Impedance	100 Ω
Max. Distance	3 m at 3840 x 2160 @ 60Hz (4:4:4)
Video Output	
Interfaces	4 x HDMI Type-A Female (Black)
Impedance	100 Ω
Max. Distance	3 m at 3840 x 2160 @ 60Hz (4:4:4)
Video	
Max. Data Rate	18 Gbps (6 Gbps per lane)
Max. Pixel Clock	600 MHz
Compliance	HDMI (3D, Deep Color, 4K) HDCP 2.2 Compatible
Max. Resolution	3840 x 2160 @ 60Hz (4:4:4)
Audio	
Input	1 x HDMI Type-A Female (Black)
Output	4 x HDMI Type-A Female (Black)
Connectors	
Power	1 x USB-C (5V/1A)
Cable Length	
USB Cable	1 x USB Type-C to Type-A (1 m)
LEDs	
LED Indicator	4 x Port Indicator (Orange)
Power	2 (Orange, Bottom Side)
Environmental	
Operating Temperature	0 – 40 °C
Storage Temperature	-20 – 60 °C
Humidity	0 – 80% RH, Non-Condensing
Physical Properties	
Housing	Plastic
Weight	0.10 kg
Dimensions (L x W x H)	14.50 x 5.65 x 1.52 cm
Carton Lot	20 pcs

Package Contents



Released: 12/2025 V1.0

© Copyright 2025 ATEN® International Co. Ltd. ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners.

Product information is subject to change without prior notice.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.