


P/G1880FS = 18U



FRONT TEMPERED GLASS DOOR OR FULLY PERFORATED DOOR



FEATURES:

- Simple and sturdy design
- Front tempered glass door with side perforation or Arc fully perforated door to enhance ventilation
- Fully perforated rear door for maximising ventilation
- Easy to dismantle front/ rear/ side doors to enable convenient operation
- Comprehensive range of sizes available
- Colour - Fully epoxy powder coated
- Can be supplied CKD

ACCESSORIES:

- Power distribution unit: Horizontal 19" rack mountable in 1U height
- Shelves: Heavy duty shelves for equipment up to 60kg
 - Cantilever shelf - available in 2U
 - Sliding shelf
 - Vented shelf
- Cooling fan
- Levelling feet
- Cable management panel: 19" panel in 1U height to provide effective cable management
- Blank/ Vented panel: Panels to cover unused space at the front of the cabinet. Available in variant sizes
- Chassis runner
- Cage nut assembly

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Volume (CBM)
P/G1880FS	18	930	600	800	970 x 612 x 812	0.4820

* P = Perforated door, G = Glass door

* Customized sizes available upon request