


P/G2480FS = 24U



FRONT TEMPERED GLASS DOOR OR FULLY PERFORATED DOOR



## FEATURES:

- Simple and sturdy design
- Front tempered glass door with side perforation or Arc fully perforated door to enhance ventilation
- Fully perforated rear door for maximising ventilation
- Easy to dismantle front/ rear/ side doors to enable convenient operation
- Comprehensive range of sizes available
- Colour - Fully epoxy powder coated
- Can be supplied CKD

## ACCESSORIES:

- Power distribution unit: Horizontal 19" rack mountable in 1U height
- Shelves: Heavy duty shelves for equipment up to 60kg
  - Cantilever shelf - available in 2U
  - Sliding shelf
  - Vented shelf
- Cooling fan
- Levelling feet
- Cable management panel: 19" panel in 1U height to provide effective cable management
- Blank/ Vented panel: Panels to cover unused space at the front of the cabinet. Available in variant sizes
- Chassis runner
- Cage nut assembly

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Volume (CBM)
P/G2480FS	24	1200	600	800	1235 x 612 x 812	0.6137

\* P = Perforated door, G = Glass door

\* Customized sizes available upon request